

FEATURE:

- Contact parts made of stainless steel.
- Precisely cast aluminum hull, smooth surface and good performance of maintaining temperature setting.
- Low noise blower, installed air filter with(optional) purity guaranteed.
- Material tank installed with side glass for inspection.
- Curve heating cylinder designed to avoid the burning caused by powder pile;
- Installed with proportional deviation display thermostat, to control temperature accurately.
- High-temperature type for 50-1500kg available, with double layer hopper tank, stainless steel heating cylinder, cooling type heater, high temperature resistance blower;
- Hopper specially designed for easy opening, suitable for all mechanical arm.

SPECIFICATIONS

| 型号 Model | 容量KG Capacity | 电热KW Heating Power | 风机W Blower | 电源V Voltage | 外形尺寸 (mm) Dimensions | 底座尺寸 (KxKxD) mm Base Size | 净重约 (KG) Approx. Net Weight |
|-------------|------------------|-----------------------|---------------|----------------|-------------------------|--------------------------------|--------------------------------|
| XC-G12KG | 12 | 1.8 | 85 | 220/2Φ | 640 x440x740 | 110x110xΦ40 | 22 |
| XC-G25KG | 25 | 3.5 | 135 | 220/2Φ | 800x420x850 | 150x150xΦ73 | 34 |
| XC-G50KG | 50 | 4.5 | 135 | 380/3Φ | 900x600x950 | 160x160xΦ73 | 45 |
| XC-G75KG | 75 | 6.5 | 210 | 380/3Φ | 900x600x1050 | 160x160xΦ73 | 56 |
| XC-G100KG | 100 | 6.5 | 215 | 380/3Φ | 1000x650x1050 | 177x177xΦ81 | 68 |
| XC-G150KG | 150 | 9 | 320 | 380/3Φ | 1300x700x1100 | 177x177xΦ81 | 78 |
| XC-G200KG | 200 | 12 | 320 | 380/3Φ | 1350x800x1400 | 200x200xΦ83 | 110 |
| XC-G300KG | 300 | 15 | 320 | 380/3Φ | 1300x900x1550 | 230x230xΦ114 | 150 |
| XC-G400KG | 400 | 15 | 410 | 380/3Φ | 1400x950x1600 | 280x280xΦ120 | 170 |
| XC-G600KG | 600 | 20 | 1030 | 380/3Φ | 1550x1150x1850 | 281x281xΦ134 | 280 |
| XC-G800KG | 800 | 30 | 2200 | 380/3Φ | 1770x1180x2540 | 280x280xΦ135 | 380 |

We reserve the right to change specifications without prior notice.