

FEATURE:

- Newly designed, small footprint and multi-functional.
- Separate control--available for maintaining three moulds or three machines with different or individual settings.
- Easy to operate and maintain, with exquisite exterior.
- Well-constructed interior pipelines with concise and well-knit designation for energy saving.
- Heating parts separated from other components to avoid damage caused by over-heat.

SPECIFICATIONS

型号Model	传热媒体 Transfer Medium	最高温度 Max. Temp.	泵功率 Pump(KW)	泵流量 Pump Flow (L/min)	泵扬程 Loading Distance (m)	发热功率 Heating Power (KW)	热媒出入口径 Inlet/Outlet Diameter	外形尺寸 Dimension (mm)	净重约 Approx.Net Weight
XC-TM6KW3S-W	清水 Water	100°C	0.37x3	42	28	6x3	3/8" × 6	810x850x663	130
XC-TM9KW3S-W			0.37x3	42	28	9x3	3/8" × 12	810x850x663	165
XC-TM12KW3S-W			0.75x3	56	38	12x3	3/8" × 12	810x850x663	185
XC-TM18KW3S-W			1.5x3	160	27	9x6	1" × 3	890x1150x753	190
XC-TM24KW3S-W			1.5x3	160	27	12x6	1" × 3	890x1150x753	230
XC-TM36KW3S-W			2.2x3	315	26	12x9	2" × 3	1016x1150x740	280
XC-TM6KW3S-O	传热油 Heat-Transfer Oil	200°C	0.37x3	33	22	6x3	3/8" × 6	1016x1150x753	130
XC-TM9KW3S-O			0.37x3	33	22	9x3	3/8" × 12	810x850x663	165
XC-TM12KW3S-O			0.75x3	45	30	12x3	3/8" × 12	810x850x663	185
XC-TM18KW3S-O			1.5x3	128	21	9x6	1" × 3	890x1150x753	190
XC-TM24KW3S-O			1.5x3	128	21	12x6	1" × 3	890x1150x753	230
XC-TM36KW3S-O			2.2x3	252	21	12x9	2" × 3	1016x1150x753	280

We reserve the right to change specifications without prior notice.