

EURO-HOPPER DRYER FEATURE:

- Microprocessor is used for accurate temperature control.
- Hot air down-blowing design ensures even distribution of hot air to maintain a steady temperature in the hopper and increase drying efficiency.
- Digital P.I.D temperature control with LED display,Innovative design with sleek appearance
- Overheat protection to ensure reliable operation.
- Automatic start/stop timer one week to improve energy saving.
- With movable materials checking door, good seal and convenient unloading (Models XCD-80U and above);
- Stainless steel tray & aluminum base as standard (Models XCD-1200U and below);application.
- Manual butterfly valve adopted (Models XCD-1500U and above);
- Escalator is optional (Models XCD-1500U and above);
- Drying hopper and hopper lid can be fully insulated for high temperature application;
- Option accessories: euro- hopper suction box, euro-hopper mobile floor stand, material door magnet, magnetic base (aluminum or stainless steel), blower inlet filter, hot air recycling, exhaust air filter;
- For European standard safety circuit type, add “CE” at model behind.

SPECIFICATIONS

型号 Model	XCD-20U	XCD-40U	XCD-80U	XCD-120U	XCD-160U	XCD-230U	XCD-300U	XCD-450U	XCD-600U	XCD-750U	XCD-900U
干燥电热 Heater Power (KW)	2.2	3	4	4.5	6	9	12	15	18	18	20
风机 Blower (KW)	0.08	0.13	0.17	0.18	0.2	0.32	0.32	0.32	0.55	0.75	0.75
料桶容量 Hopper Capacity (L)	20	40	80	120	160	230	300	450	600	750	900
外形尺寸 (mm) Dimensions H x W x D	730 x 575 x 325	760 x 640 x 390	940 x 722 x 475	1210 x 722 x 475	1225 x 822 x 575	1505 x 822 x 575	1450 x 945 x 695	1850 x 945 x 695	1820 x 1170 x 915	2100 x 1170 x 915	2070 x 1340 x 1050
脚架尺寸 (mm) Floor Stand H x W x D	790 x 450 x 550	790 x 450 x 550	840 x 552 x 722	840 x 552 x 722	920 x 662 x 795	920 x 662 x 795	970 x 790 x 930	970 x 790 x 930	1130 x 1000 x 1200	1130 x 1000 x 1200	1320 x 1200 x 1200
整体高度 (mm) Whole Height	1260	1295	1465	1735	1825	2105	2085	2435	2470	2780	2730
排风口径 Air Inlet Pipe Diameter	2"		2.5"		3"			4"			
出风管口径 Air Inlet Pipe Diameter	1.5"		2"		2.5"			3"		4"	
风机脚架尺寸 (mm) Blower Stand H3 x W3 x D3											
净重约 (KG) Approx.Net Weight	40	45	50	60	90	100	130	160	200	220	250

型号 Model	XCD-1200U	XCD-1500U	XCD-2300U	XCD-2500U	XCD-3000U	XCD-4000U	XCD-4500U	XCD-6000U
干燥电热 Process Heater(Power)	30	32	42	48	48	64	80	96
风机 Blower (KW)	1.5	1.5	2.2	2.2	2.2	3.75	3.75	5.5
料桶容量 Hopper Capacity (L)	1200	1500	2300	2500	3000	4000	4500	6000
外形尺寸 (mm) Dimensions H x W x D	2500 x 1340 x 1050	2950x1542x1250	3350x1542x1250	3510x1770x1400	3910x1770x1400	4050x1980x1600	4350x1980x1600	4350x2220x1800
脚架尺寸 (mm) Floor Stand H x W x D	1320 x 1200 x 1200	1400x1500x1500	1400x1500x1500	1500x1640x1640	1500x1640x1640	1650x1900x1900	1650x1900x1900	1650x2100x2100
整体高度 (mm) Whole Height	3160	3470	3870	4050	4400	4550	4850	5100
排风口径 Air Inlet Pipe Diameter	4"	5"		6"		8"		
出风管口径 Air Inlet Pipe Diameter	4"	5"		6"		8"		
风机脚架尺寸 (mm) Blower Stand H3 x W3 x D3		1210x560x700	1210x560x700	1210x560x700	1210x560x700	1400x600x800	1400x600x800	1450x780x850
净重约 (KG) Approx.Net Weight	380	495	570	620	700	860	940	1210

Note: 1)For polished hopper inside,plus “P” at model behind.
2)Mark “HT” at the back of models when 180 high-temp is requested.
3)Blower is included in machine net weight,but floor stand is not included.
4)Power supply:3Φ ,380V,50Hz.

We reserve the right to change specifications without prior notice.